

LOOKING FOR ONE FOR ALL SAFETY HARNESS?

Honeywell Miller® HD Harness offers you comfort and convenience you need to complete your jobs in different applications confidently.

QuickPick
Rescue/Descent

SafEscape
Rescue/Descent

Vi-Go
Vertical Ladder
Safety System

VR500
GlideLoc Shuttle

HD 2Pt Harness
Twin Shock
Absorbing Lanyard

3Pod Tripod
Confined Space
Descent/Rescue

Edge Rope Grab
RG300 & RG500

DuraHoist
Confined Space
Descent/Rescue

1 FOR 5 APPLICATIONS

accommodates a variety of all fall protection applications (Fall Arrest, Ladder Climbing System, Rope Grab, Confined Space and Rescue Systems)

A NEW FEELING OF SAFETY AT HEIGHT

H-TYPE HARNESS - 2PT

Comfort, easy and quick adjustability & connection, greater safety and easier traceability.

Lanyard Keeper
Attach lanyard when not in use to avoid tripping hazard

Front D Ring
• Easy connection and facilitates
• Easy rescue operation

H-Type Harness
The force will transmit vertically over two straps to thigh

Friction - Mating Buckles
Easy to adjust, non slip design

Greater Visibility and Safety
Fluro - Orange textile, with high visible stitching to facilitate visual inspection before working

Patented Reinforced Structure
For high strength

Adjustable Plastic Pad
For a perfect fit

Extra Size Back D-Ring
• Easy connection and facilitates
• Easy rescue operation

Fall Indicator
Indicates the fitness of the harness and facilitates easy periodical inspections

Sealed Label Cover
Protects the product from UV, dust and external wear and tear

HD SHOCK ABSORBING LANYARD

Shock Absorber pack is designed with a specially-woven inner core that smoothly expands to reduce fall arrest forces.

Shock Absorber
Heated treated shrink packed transparent cover shock absorber

Karabiner
Screw lock galvanized steel 17mm opening

Rebar Hook
Auto lock galvanized steel 53mm opening scaffolding hooks

Reinforced Webbing Protection
Extra polyester cover reinforced to ends avoid wear

Polyester Webbing
New vibrant Hi-Viz 45mm webbing to avoid entanglements

Product Label
UV protected labels which withstands hard environmental conditons

Min. Clearance: 6.2M
Capacity: 100 kg

CERTIFICATIONS

- EN 355
- JIS T 8165:2018

Honeywell Personal Protective Equipment

Level 25, UOA Corporate Tower
Lobby B, The Vertical, Bangsar South City
59200 Kuala Lumpur, Malaysia
Tel: +603-2777 3948 / 3950
Email: hsp.asean@Honeywell.com

www.honeywellsafety.com

FALL-PROTECTION-ASEAN-INFOGRAPHIC_12/20
© 2020 Honeywell International Inc.

Honeywell
MILLER®