

## GLOVE BAGS, GLOVE INFLATOR AND DIELECTRIC FOOTWEAR

### SHOCK PROTECTION

**GLOVE BAGS** - Salisbury bags are constructed of heavy duty canvas duck and are double stitched at stress points for extra durability. Canvas bags feature a snap hook for hanging on work belts. Bags feature tapered gussets with wide opening tops for easy insertion.

#### PRODUCT NUMBERING CHART FOR GLOVE BAGS

CAT. NO.	GLOVE Length in. (mm)	DIMENSIONS in (mm)	WEIGHT lbs. (kgs)
GB112	11 (280)	9" X 14" (229 X 356)	1 (.5)
GB114	14 (356)	9" X 16" (229 X 406)	1 (.5)
GB116	16 (406)	9" X 18" (229 X 457)	1.2 (.6)
GB118	18 (457)	9" X 20" (229 X 508)	1.5 (.7)

**GLOVE INFLATOR** - Electrical insulating gloves must be inspected before each use. Inspection is simplified by using a portable glove inflator such as the Salisbury G99 and the G100 with adapter for Class 00 and 0 and smaller size gloves. The Patented G99 is a simple, easy to use, portable glove inflator. The G99 provides a quality means of inspecting gloves in the field. The glove is secured to the inflator using a nylon strap and fastened with hook and pile. Inflation is accomplished by pumping the bellows of the inflator.

#### GLOVE INFLATOR

CAT. NO.	DESCRIPTION	WEIGHT lbs. (kgs)
G99	Glove inflator kit	2 (.91)
G99B	Replacement bag	-
G99S	Replacement strap	-
G99V	Replacement check valve	-
G100	Glove inflator kit w/ adapter	-
G100A	Small low-volt glove adapter	-

**ASTM DIELECTRIC FOOTWEAR - 100% TESTED TO 20KV** - Salisbury's ASTM dielectric footwear is 100% waterproof and made from premium grade, ozone resistant rubber. The flexible hand-layered construction includes a durable, nylon lining for easy on/off. The sole has a durable construction with a non-skid, bar tread outsole. The attached buckle and hardware is nonmetallic. All of Salisbury's ASTM Dielectric Footwear conforms with ASTM F2413 and is 100% tested to the electrical hazard requirements of ASTM F2413 at 20,000 volts.

#### DIELECTRIC FOOTWEAR

CAT. NO.	DESCRIPTION	SIZES	WEIGHT PR. lbs. (kgs)
21402	17", 1 Buckle overboot	Whole sizes 7 - 17	5.8 (2.6)
51530	2-Buckle Overshoe	Whole sizes 6 - 17	4.4 (.2)
51581	Non-buckle overshoe	Whole sizes 7 - 17	3.3 (1.5)
31924	11" 4-Buckle Artic Overboot	Whole sizes 6 - 17	4.6 (2.1)
51824	Storm Rubber Overshoe	Whole sizes 7 - 16	3.25 (1.5)
31910	11" 4 Buckle Overboot-V-Grip	Whole sizes 7 - 17	3.8 (1.7)
51510	Deep Heel Rubber Overshoe	Whole sizes 6 - 12	3.1 (1.4)

**NOTE:** When ordering, add size as suffix to part number. Be sure to add a space between the part number and size. Example: 51511 7

GB114



G99



**G100 WITH INFLATED LOW-VOLT GLOVE READY FOR INSPECTION.**

G100



21402



31924



31910



**SERVUS**  
by Honeywell

51824



51530



51581



51510

