



MILLER MIGHTEVAC® SELF-RETRACTING LIFELINES WITH EMERGENCY RETRIEVAL HOIST

Miller MightEvac Self-Retracting Lifelines combine the superior performance and reliability of the best-selling MightyLite Self-Retracting Lifeline Series with a quick-activating retrieval mechanism for emergency evacuation.

- 20% lighter than competitive models provides significant long-term savings and lowers cost of ownership
- Promotes quick and easy rescue with a 4:1 mechanical advantage (average speed of 25ft [8 m] per minute)
- For emergency evacuation only
- Corrosion-resistant stainless steel & aluminum components
- Convenient, heavy-duty carrying handle
- 310 lbs (140.6kg) working capacity

Available in galvanized or stainless steel cable in lengths of 50ft (15m), 100ft (30m) and 130ft (40m). Kevlar rope models available in lengths of 40ft (12m) MR40KB-Z7/40FT, and 80ft (24m) MR80KB-Z7/80FT.

REF.	DESCRIPTION	WEIGHT
MR50GB-Z7/50FT	MightEvac w/50ft (15m) of 0.2 inch (5mm) Galvanized Cable w/Mounting Bracket & Pulley	39 lbs (18kg)
MR100GB-Z7/100FT	MightEvac w/100ft (30m) of 0.2 inch (5mm) Galvanized Cable w/Mounting Bracket & Pulley	59 lbs (27kg)
MR50SB-Z7/50FT	MightEvac w/50ft (15m) of 0.2 inch (5mm) Stainless Steel Cable w/Mounting Bracket & Pulley	39 lbs (18kg)

Note: Locking Snap Hook - 0.75 inch (19mm) gate opening. All connectors include 3,600 lbs gate-strength.

MILLER MANHANDLER® HOIST/WINCH

The Miller ManHandler Hoist/Winch is the perfect solution for a range of applications including confined space entry, rescue, positioning and personnel/material handling.

A secondary fall arrest system is recommended for fall protection.

- Compact, durable steel construction
- Smooth, controlled winding action
- Effortless lifting and lowering with 5:1 gear ratio
- Anti-backlash crank handle braking system prevents freewheeling
- Built-in mounting bracket
- 350 lbs (159kg) working capacity





REF.	DESCRIPTION
8442-Z7/65FT	ManHandler Hoist w/65ft (20m) of 0.2 inch (5mm) Galvanized Cable
8442-Z7/100FT	ManHandler Hoist w/100ft (33 m) of 0.2 inch (5mm) Galvanized Cable

* Also available with stainless steel cable by adding "SS" after the model number (Ex: 8442SS-Z7/65FT). Note: Locking Snap Hook - 0.75 inch (19mm) gate opening. All connectors include 3,600 lbs gate-strength.