



PERSONAL FALL LIMITERS (PFL)

MILLER TURBOLITE™ EDGE SERIES

Honeywell's extensive series of Miller TurboLite Personal Fall Limiters (PFLs) is even more versatile with the introduction of the TurboLite Edge Series.

Whether you work in construction, industrial, or even wind power, units for sharp and smooth edges including options for tie-back applications will help you ensure workers are safe in applications requiring foot-level tie-off or work near edges.

MAKE CONFIDENCE YOUR TRUE EDGE

TurboLite Edge PFLs are engineered to deliver the assurance you expect from Miller Fall Protection, in a wide range of lengths and innovative features:

- Safe – Models are available for sharp and smooth edges. Sharp Edge models are ANSI Leading Edge certified for edges with a radius ≥ 0.005 inch (0.13mm). Smooth Edge models are designed for a radius ≥ 0.060 inch (1.5mm)
- Versatile – Can be used for foot-level tie-off or anchored overhead as a traditional SRL for workers up to 420 lbs.
- Compact and Lightweight – Reduce fatigue, increase productivity
- Simple – Easy to install, easy to use
- Superior Mobility – Integral swivel design prevents lifeline from twisting
- Durable – High-impact nylon housing and abrasion resistant webbing
- Reliable – Durable design with integral shock absorber with the ability to repair and replace
- Configurable – A broad range of working lengths featuring cable, web, and tie-back options with a wide variety of lifeline connectors
- Twin Models available – Provides 100% tie-off connection

The TurboLite Edge Series is available in both web and galvanized cable lifeline options, in working lengths that range from 6–12ft (1.8–3.7m).

Note: All connectors include 3,600-lbs gate-strength



MILLER TURBOLITE™ EXTREME

Cable Lifeline for Sharp Edge Applications

- Designed for use in sharp edge applications with radius ≥ 0.005 in (0.13 mm)
- Meets ANSI Z359.14 Class B and Leading Edge requirements
- Galvanized cable lifeline

REF.	LENGTH	WEIGHT	SINGLE OR TWIN	LIFELINE CONNECTORS(S)
MFLEC-3/6FT	6ft	4.0 lbs (1.8kg)	Single	Steel Locking Snap Hook
MFLEC-12/6FT	6ft	4.5 lbs (2.0kg)	Single	Aluminum Locking Rebar Hook
MFLEC2-3/6FT	6ft	6.9 lbs (3.1kg)	Twin	Steel Locking Snap Hooks
MFLEC2-4/6FT	6ft	8.8 lbs (4.0kg)	Twin	Steel Locking Rebar Hooks
MFLEC2-12/6FT	6ft	8.0 lbs (3.6kg)	Twin	Aluminum Locking Rebar Hooks
MFLEC-3/9FT	9ft	4.2 lbs (1.9kg)	Single	Steel Locking Snap Hook
MFLEC-12/9FT	9ft	4.7 lbs (2.1kg)	Single	Aluminum Locking Rebar Hook
MFLEC2-3/9FT	9ft	7.3 lbs (3.3kg)	Twin	Steel Locking Snap Hooks
MFLEC2-4/9FT	9ft	9.1 lbs (4.1kg)	Twin	Steel Locking Rebar Hooks
MFLEC2-12/9FT	9ft	8.3 lbs (3.8kg)	Twin	Aluminum Locking Rebar Hooks



MFLEC2-12/6FT



MILLER TURBOLITE™ MAX

Web Lifeline for Smooth Edge Applications

- Designed for use in smooth edge applications with radius ≥ 0.060 inch (1.5mm)
- Meets ANSI Z359.14 Class B requirements
- Honeywell Spectra® webbing lifeline provides outstanding chemical, abrasion, and cut resistance

REF.	LENGTH	WEIGHT	SINGLE OR TWIN	LIFELINE CONNECTORS(S)
MFLEW-3/6FT	6ft	3.5 lbs (1.6kg)	Single	Steel Locking Snap Hook
MFLEW-12/6FT	6ft	6.9 lbs (3.1kg)	Twin	Aluminum Locking Rebar Hook
MFLEC-3/9FT	9ft	3.5 lbs (1.6kg)	Single	Steel Locking Snap Hook
MFLEC-12/9FT	6ft	7.0 lbs (3.2kg)	Twin	Aluminum Locking Rebar Hook
MFLEW-3/12FT	12ft	3.6 lbs (1.6kg)	Single	Steel Locking Snap Hook
MFLEW-2-12/12FT	12ft	7.1 lbs (3.2kg)	Twin	Aluminum Locking Rebar Hook



MFLEW2-12/6FT