



MILLER TURBOLITE™ PERSONAL FALL LIMITERS

The cost-effective and competitive pricing of the Miller TurboLite Personal Fall Limiters will make shock-absorbing lanyards obsolete on the job site. Workers will no longer need to “switch-out” equipment to maintain a safe fall distance.

- First affordable alternative to shock-absorbing lanyards
- Extremely compact and lightweight
- Available in 6ft (1.8m) and 9ft (2.7m) working lengths
- Unit attaches directly to the harness back D-ring for greater mobility and versatility
- Engineered webbing for greater abrasion resistance and longer service life
- High-strength, impact-resistant nylon housing for maximum durability
- Built-in swivel prevents lifeline from twisting
- Rated for up to a 400 lbs (181.4kg) worker
- No annual factory recertification required



MFL-1-Z7/6FT

MFL-1-Z7/9FT

REF.	LENGTH	WEIGHT	UNIT CONNECTOR	LANYARD END CONNECTOR
MFL-1-Z7/6FT	6ft	2.5 lbs (1.1kg)	Steel Karabiner	Steel Locking Snap Hook
MFL-2-Z7/6FT	6ft	3.4 lbs (1.5kg)	Steel Karabiner	Steel Locking Rebar Hook
MFL-9-Z7/6FT	6ft	2.7 lbs (1.2kg)	Steel Locking Snap Hook	Steel Locking Snap Hook
MFL-11-Z7/6FT	6ft	1.9 lbs (0.86kg)	Aluminum Karabiner	Aluminum Locking Snap Hook
MFL-12-Z7/6FT	6ft	2.6 lbs (1.2kg)	Aluminum Karabiner	Aluminum Locking Rebar Hook
MFL-1-Z7/9FT	9ft	2.9 lbs (1.3kg)	Steel Karabiner	Steel Locking Snap Hook
MFL-9-Z7/9FT	9ft	3.1 lbs (1.4kg)	Steel Locking Snap Hook	Steel Locking Snap Hook
MFL-11-Z7/9FT	9ft	2.5 lbs (1.1kg)	Aluminum Karabiner	Aluminum Locking Snap Hook
MFL-12-Z7/9FT	9ft	3.4 lbs (1.5kg)	Aluminum Karabiner	Aluminum Locking Rebar Hook

Note: Locking snap hook – 0.75 inch (19mm) gate opening. Locking rebar hook – 2.5 inches (63mm) gate opening. All connectors include 3,600 lbs gate-strength.



Steel Karabiner



Aluminum Karabiner



Without Unit Connector



Aluminum Locking Rebar Hook



Steel Locking Rebar Hook



Steel Locking Swivel Snap Hook



Steel Locking Snap Hook



Aluminum Locking Snap Hook



Steel Locking Swivel Rebar Hook



D-Ring Swivel Hook



MILLER TWIN TURBO™ FALL PROTECTION SYSTEMS WITH G2 CONNECTOR

New patent-pending Miller Twin Turbo™ G2 Connector easily adapts two lightweight Miller TurboLite™ Personal Fall Limiters for continuous 100% tie-off fall protection.

- Better alternative to double-leg lanyards – Reduces fall clearance requirements for use in more applications
- Ultimate Mobility – PFLs swivel independently to prevent webbing from twisting and binding in the unit
- Lightest-weight Twin Connector on the market – Increases productivity by reducing worker fatigue
- Superior durability – Corrosion resistant aluminum connector and high-impact nylon result in a longer product life
- Superior safety – Webbing Retainer Clip rotates freely to prevent unintentional opening of carabiner gate
- D-Pad Clip – Maintains harness adjustment while working by keeping the harness webbing and D-Pad in place
- Connects to harness webbing below D-ring – Frees harness D-ring for rescue and connection to an overhead SRL
- Webbing Retainer Clip accommodates thicker webbing designs for more versatility and easy insertion of the webbing



MFLC/



MFLT-1/7.5FT



MFLC-12-Z7/9FT

REF.	LENGTH	WEIGHT	UNIT CONNECTOR	LANYARD END CONNECTOR
MFLC-12-Z7/6FT	6ft	5.8 lbs (2.6kg)	Twin Turbo G2 Connector	Aluminium Locking Rebar Hooks
MFLC-12-Z7/9FT	9ft	6.6 lbs (2.9kg)	Twin Turbo G2 Connector	Aluminium Locking Rebar Hooks
Twin Turbo G2 Connector And Components				
MFLC/	-	0.37 lbs (0.17kg)	Twin Turbo G2 Connector Kit - includes MFLC-1/, MFLC-2/, and MFLC-3/	-
MFLC-1/	-	0.29 lbs (0.13kg)	Aluminium Karabiner	-
MFLC-2/	-	0.04 lbs (0.02kg)	G2 Webbing Retainer Clip	-
MFLC-3/	-	0.04 lbs (0.02kg)	G2 D-Pad Connector Clip	-

Note: All connectors include 3,600-lbs gate-strength